

# Distribution Model XH200

Permanent installation 200W+200W power amplifier  
with great sound  
Light & compact 2U size with current switching

**NEW**

Switching  
Power Supply

2U  
Light  
Weight



## XH200

- XH200 featuring a 2-channel high-impedance power amplifier (200W/24 ohms @70V, 200W/48 ohms @100V).
- The current switching allows for a compact and lightweight design (10kg). This series utilizes the newly developed 2U shell.
- Highly precise dB display detented attenuators, dedicated to each channel, are located on the front panel. The models also feature a protection circuit that allows you to monitor its status with an indicator. Attention to detail for better practicality can be found wherever you look.
- Equipped with Euro-block inputs and barrier strip terminal outputs. Also equipped with monitor/remote terminals and a subsonic filter. The models have been designed with all sorts of usage in mind.


### SPECIFICATIONS

Model	XH200	
Power Output Level	RL=24Ω (70V)	200W x 2
	RL=48Ω (100V)	200W x 2
THD+N=0.1%		
1/8 Power Consumption (4Ω)		250W
Dimensions (W x H x D)	480 x 88 x 412.2 mm (18-7/8" x 3-1/2" x 16-1/4")	
Weight	10kg (22 lbs.)	

### REAR PANEL



### DIMENSIONS



### BLOCK DIAGRAM

